

STEINLINGE



UP TO DATE.
VISIBLE BRICKWORK WITH
ANTIQUE LOOK.
MODERN HANDLING.



ANTIQUE LOOK WITH EASY-TO-LAY, RELIABLE SIZING; ENERGY-CONSCIOUS MYTH APPEARANCE.

Steinlinge are the descendants, adapted to contemporary clinker standards of the fine old brick era. Steinlinge give a facade the charm of times gone by, while they are at the same time easy to lay thanks to their uniform size.

Fired to be frostproof in high-tech sintering furnaces at 1.300 °C, Steinlinge continue the tradition of masonry with added weatherproofing. These brick veneers are not only permanently easy to clean and use, but in combination with an EIFS system, they are also compliant with all current energy-saving regulations.

STEINLINGE

HAND-MADE LOOK. EXACTLY SIZED. MYTHICAL.

FIRINGS AND FORMAT



371 silberbeige
Δ < 3 % · DIN EN 14411, Gr. AII₀



372 amberbeige
Δ < 3 % · DIN EN 14411, Gr. AII₀



374 shabbyrot
Δ < 3 % · DIN EN 14411, Gr. AII₀



375 platingrau
Δ < 3 % · DIN EN 14411, Gr. AII₀



376 platinschwarz
Δ < 6 % · DIN EN 14411, Gr. AII₀ - Part 1



377 platinbraun
Δ < 3 % · DIN EN 14411, Gr. AII₀



PRODUCT DETAILS

STEINLINGE

DIN EN 14411



format no.	7370	7371
description	clinker brick slips	corner ¹⁾
nominal size (cm)	NF	NF
production size (mm)	240 x 71 x 14	240 x 115 x 71 x 14
371 silberbeige 372 amberbeige 374 shabbyrot 375 platingrau 376 platin schwarz 377 platinbraun	★ PG 39 ●	★ PG 772 ●
pieces per bundle	18	14
pieces per m ² /rm incl. joint	48,00	12,50
pieces per pallet	2.070	910
m ² /rm per bundle	0,38	1,12
m ² /rm per pallet	43,13	72,80
bundles per pallet	115	65
kg per pallet	1.062	715
kg per piece	0,513	0,786
kg per m ² /rm	24,624	9,825
kg per bundle	9,234	11,004
surcharge	❖	❖

- ★ = Discount on pallets.
- = Normally available ex stock.
- PG = Price group (please see current price list).
- ❖ = Minimum quantity: each open box will incur a surcharge.
- ¹⁾ = The Ströher standard for angular accuracy in angled brick slips is based on the DIN 105 standard for exposed clinker brickwork, but with only 50% of the permissible tolerance values. The Ströher specification is thus +/- 1°. This equates to a maximum deviation of +/- 4 mm on the stretcher side and +/- 2 mm on the header side for a corner with the 240 x 115 mm format.

The formats shown are illustrative drawings and are not binding. All information without guarantee.

* Ströher is the only German manufacturer offering a 25-year frost resistance guarantee on the following extruded products that have been correctly installed by a qualified professional tiler: Keraplatte® Selected, Keraplatte® Zoé, Keraplatte® Gravel Blend, Keraplatte® Epos, Keraplatte® Aera T, Keraplatte® Aera, Keraplatte® Roccia X, Keraplatte® Roccia, Keraplatte® Asar, Keraplatte® Terra, Keraplatte® Duro, Terrace slab TerioTec® X Profile, Terrace slab TerioTec® X, Terrace Slab TerioTec®, Stalotec®, Brickwerk, Brick 60, Wasserbrand, Kontur, Stiltreu, Riegel 50, Handstrich, Steinlinge, Glanzstücke, Zeitlos, Keraprotect® and Keravette®. Please find further explanations in our general terms and conditions.

